Date Prepared: 09/13/2017

MSDS No: SM5731 Date Revised: 11/07/2017

Revision No: 4

PERMATHANE SM5731 Silicone Sealant

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PERMATHANE SM5731 Silicone Sealant

MANUFACTURER

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

Holcim Solutions and Products US, LLC 26 Century Boulevard, Suite 205 Nashville, Tennessee 37214 1-800-878-7876 • www.holcimpermathane.com

COMMENTS: PERMATHANE is a registered trademark of Holcim Solutions and Products US, LLC.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Acute Toxicity (Dermal), Category 4
Serious Eye Damage, Category 1
Skin Sensitization, Category 1
Carcinogenicity, Category 2

GHS LABEL



Health hazard



Corrosion



Exclamation mark

SIGNAL WORD: DANGER HAZARD STATEMENTS

H312: Harmful in contact with skin.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H351: Suspected of causing cancer.

PRECAUTIONARY STATEMENT(S)

Prevention:

[201]: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER/doctor.

Date Prepared: 09/13/2017 MSDS No: SM5731 Date Revised: 11/07/2017

Revision No: 4

PERMATHANE SM5731 Silicone Sealant

P322: Specific measures are required.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P363: Wash contaminated clothing before reuse.

P370+P378: In case of fire: Use appropriate media to extinguish.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

EMERGENCY OVERVIEW

PHYSICAL APPEARANCE: Viscous Liquid. Grey Sealant.

IMMEDIATE CONCERNS: CAUTION! May cause eye, skin, nose and throat irritation.

POTENTIAL HEALTH EFFECTS

EYES: Contact may cause moderate eye irritation.

SKIN: Repeated or prolonged skin contact may result in allergic dermatitis. If product is hot, contact with the skin will result in thermal burns.

INGESTION: Not likely route of entry. **INHALATION:** Not likely route of entry.

ROUTES OF ENTRY: Eye and skin contact. Inhalation and ingestion are unlikely routes of entry.

IRRITANCY: Eye and skin irritation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
2-butanone Oxime	< 2	96-29-7

4. FIRST AID MEASURES

EYES: Flush eye with tempered water for 15 minutes lifting upper and lower eye lids occasionally. If irritation persists, contact a physician.

SKIN: Remove contaminated clothing. Immediately wash exposed area with large amounts of water. If hot material adheres to the skin, do not attempt to peal off material. Cool the hot material with water and cover with a dry sterile dressing. Seek medical attention.

INGESTION: Do not induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

INHALATION: Under normal conditions of use, inhalation of product is unlikely. If fumes are inhaled and become irritant, remove person from the area to fresh air. Seek immediate medical attention if exposure has occurred.

NOTES TO PHYSICIAN: Treat symptomatically.

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: None

GENERAL HAZARD: Non Hazardous

Date Prepared: 09/13/2017 MSDS No: SM5731 Date Revised: 11/07/2017

Revision No: 4

PERMATHANE SM5731 Silicone Sealant

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide, or fine.

EXPLOSION HAZARDS: Low hazard

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus with pressure-demand,

full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: This material is a solid product and release to the environment is highly unlikely. Containment is not necessary, this product will not flow. Use appropriate personal protective equipment (PPE) when handling product. Only employees properly trained should be part of any containment or spill response.

LARGE SPILL: Refer to release measures under small spill, large spills are to be handled in the same manner.

7. HANDLING AND STORAGE

HANDLING: Use good chemcial handling procedures and practices. No special handling precautions are required.

STORAGE: Store at or under 80 degrees F. Do not stack cartons on end. Rotate stock.

SHELF LIFE: 9 months from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)						
	EXPOSURE LIMITS					
Chemical Name	Туре		ppm	mg/m³		
2-butanone Oxime	OCUA DEL	TWA	NL [1]	NL [1]		
	OSHA PEL	STEL	NL [1]	NL [1]		
	ACCTU TUV	TWA	NL [1]	NL [1]		
	ACGIH TLV	STEL	NL [1]	NL ^[1]		

Footnotes:

1. NL = Not Listed

ENGINEERING CONTROLS: Natural ventilation should be adequate under normal conditions.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields.

SKIN: Wear chemical resistant, impervious gloves.

RESPIRATORY: No respiratory protection required under normal conditions.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly

after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Paste

ODOR: Slight

Date Prepared: 09/13/2017 MSDS No: SM5731 Date Revised: 11/07/2017

Revision No: 4

PERMATHANE SM5731 Silicone Sealant

ODOR THRESHOLD: Not Determined

COLOR: Various

pH: 7.02

PERCENT VOLATILE: 4.2

FLASHPOINT AND METHOD: Not Applicable

FLAMMABLE LIMITS: No data

AUTOIGNITION TEMPERATURE: Not Applicable

VAPOR PRESSURE: Not Determined
VAPOR DENSITY: Not Determined
BOILING POINT: Not Determined
FREEZING POINT: Not Determined
MELTING POINT: Not Determined
SOLUBILITY IN WATER: Nonsoluble

PARTITION COEFFICIENT: N-OCTANOL/WATER: Not Determined

EVAPORATION RATE: Not Determined

DENSITY: 8.42 lbs/gal
SPECIFIC GRAVITY: 1.01
VISCOSITY: Not Determined

(VOC): 41.9 gr/L EPA Method 24 VOC

10. STABILITY AND REACTIVITY

REACTIVITY: Yes

HAZARDOUS POLYMERIZATION: Product will not undergo polymerization.

STABILITY: Stable.

CONDITIONS TO AVOID: No conditions known
POSSIBILITY OF HAZARDOUS REACTIONS: None

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, hydrogen chloride and sulfides.

INCOMPATIBLE MATERIALS: Liquid chlorine, potassium permanganate, fuming nitric acid, fluorine and other

strong oxidizing and base agents.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)
2-butanone Oxime	2326 mg/kg (rats)	2702 mg/kg (rat) - Subcutaneous

NOTES: No known acute effects.

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No environmental information was found for this product.

Date Prepared : 09/13/2017 **MSDS No :** SM5731

Date Revised: 11/07/2017 **Revision No:** 4

PERMATHANE SM5731 Silicone Sealant

ECOTOXICOLOGICAL INFORMATION: No ecotoxicity data was found for this product.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Consult with your state and local hazardous waste requirements or guidelines to ensure compliance. Arrange disposal in accordance with EPA, state and local requirements.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not Regulated for Transport **PRIMARY HAZARD CLASS/DIVISION:** Not Regulated

UN/NA NUMBER: NA
PACKING GROUP: NA

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: No PRESSURE GENERATING: No REACTIVITY: No ACUTE: No CHRONIC: No

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
2-butanone Oxime	96-29-7


16. OTHER INFORMATION

Date Revised: 11/07/2017

INFORMATION CONTACT: (972) 438-9111

REVISION SUMMARY: This MSDS replaces the 09/13/2017 MSDS. Revised: **Section 9:** DENSITY, MOLECULAR WEIGHT, OXIDIZING PROPERTIES, PARTICLE SIZE, PERCENT VOLATILE, POUR POINT, SPECIFIC GRAVITY,

SPECIFIC VOLUME, (VOC).





GENERAL STATEMENTS: Keep out of reach of children

For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication

Date Prepared: 09/13/2017 MSDS No: SM5731 Date Revised: 11/07/2017

Revision No: 4

PERMATHANE SM5731 Silicone Sealant

Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Holcim Solutions and Products US, LLC. The data on this sheet relates only to the specific material designated herein. Holcim Solutions and Products US, LLC assumes no legal responsibility for use or reliance upon these data.