In accordance with OSHA 29 CFR 1910.1200

SM7713 MS BLACK Revision Number 1 Revision date 02-Apr-2021 Supersedes Date: Not applicable

PERMATHANE SM7713 MS Silyl-Modified Adhesive Sealant

1. Identification

1.1. Product Identifier

Product Name SM7713 MS BLACK

Other means of identification

Other information Not applicable

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants Restrictions on use No information available

1.3. Details of the supplier of the safety data sheet

Responsible Party

ITW Polymers Sealants North America 12055 Cutten Road, Houston, TX 77066

Tel: 972-438-9111

1.4. Emergency telephone number

Emergency Telephone CHEMTREC (US Transportation): (800) 424-9300

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Skin sensitization	Category 1
Reproductive toxicity	Category 1B

Hazards not otherwise classified (HNOC)

Not applicable

2.2. Label Elements

EMERGENCY OVERVIEW

Danger

Hazard statements

May cause an allergic skin reaction May damage fertility or the unborn child

US - EN Page 1/12

SM7713 MS BLACK Revision Number 1 Revision date 02-Apr-2021 Supersedes Date: 08-Jan-2021



Appearance Paste Physical state Solid Odor Odorless

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Contaminated work clothing should not be allowed out of the workplace
Wear protective gloves

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/ container to an approved waste disposal plant

0 % of the mixture consists of ingredient(s) of unknown toxicity

2.3. Other Information

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

3. Composition/information on ingredients

3.1. Substances

Not applicable.

Mixture

Chemical name	CAS No	Weight-%
Limestone	1317-65-3	30 - 60
Carbonic acid, calcium salt (1:1)	471-34-1	1 - <5
Trimethoxyvinylsilane	2768-02-7	1 - <5
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.1 - <1
Carbon black	1333-86-4	0.1 - <1
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	22673-19-4	0.1 - <1

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. First-aid measures

US - EN Page 2/12

SM7713 MS BLACK
Revision Number 1 Revision date 02-Apr-2021
Supersedes Date: 08-Jan-2021

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety data

sheet to the doctor in attendance.

Inhalation Remove to fresh air. If symptoms persist, call a physician.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If symptoms persist,

call a physician.

Skin contact Immediately flush eyes or skin with plenty of water for at least 15 minutes while removing

contaminated clothing and shoes. Wash contaminated clothing before reuse. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion If swallowed, call a poison control center or physician immediately. Rinse mouth. Do not

induce vomiting without medical advice. Small amounts of toxic methanol are released by

hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergic skin reaction. May cause sensitization by skin contact. Itching. Rashes.

Hives.

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing. Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Use extinguishing

measures that are appropriate to local circumstances and the surrounding environment.

CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Large Fire

Thermal decomposition can lead to release of irritating gases and vapors. Product is or

contains a sensitizer. May cause sensitization by skin contact.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2).

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

US - EN Page 3/12

SM7713 MS BLACK
Revision Number 1 Supersedes Date: 02-Apr-2021
Supersedes Date: 08-Jan-2021

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapors/spray. Wash

thoroughly after handling. Do not touch or walk through spilled material.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. Do not allow to enter

into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up

Use personal protective equipment as required. Cover liquid spill with sand, earth or other

noncombustible absorbent material. Take up mechanically, placing in appropriate

containers for disposal. Clean contaminated surface thoroughly.

Reference to other sections See section 8 for more information. See section 13 for more information.

7. Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protective equipment as required. Handle in accordance with good industrial

hygiene and safety practice. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before

reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep/store only in original container. Keep away from food, drink and animal feeding stuffs.

Protect from sunlight. Store in a well-ventilated place. Keep at temperatures between 41

and 95 °F. Protect from moisture.

7.3 References to other sections

Reference to other sections Section 10: STABILITY AND REACTIVITY

Section 13: DISPOSAL CONSIDERATIONS

8. Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

US - EN Page 4/12

SM7713 MS BLACK Revision Number 1 Revision date 02-Apr-2021 Supersedes Date: 08-Jan-2021

curing. The components of this product are inextricably bound in a polymer matrix and are not expected to be available as airborne hazards (dust, mist, or spray) under normal condition of use.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Limestone 1317-65-3	-	TWA: 15 mg/m³ total dust TWA: 5 mg/m³ respirable fraction	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
		(vacated) TWA: 15 mg/m³ total dust (vacated) TWA: 5 mg/m³ respirable fraction	
Carbonic acid, calcium salt (1:1) 471-34-1	-	-	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust
Carbon black 1333-86-4	TWA: 3 mg/m³ inhalable particulate matter	TWA: 3.5 mg/m³ (vacated) TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	STEL: 0.2 mg/m³ Sn TWA: 0.1 mg/m³ Sn S*	TWA: 0.1 mg/m³ Sn (vacated) TWA: 0.1 mg/m³ Sn (vacated) S*	IDLH: 25 mg/m³ Sn TWA: 0.1 mg/m³ except Cyhexatin Sn

Chemical name	Argentina	Brazil	Chile	Colombia
Limestone 1317-65-3	TWA: 10 mg/m ³	-	TWA: 7 mg/m ³	-
Carbon black 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	-	TWA: 3mg/m ³
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	TWA: 0.1 mg/m³ Skin STEL: 0.2 mg/m³	TWA: 0.1 mg/m ³	TWA: 0.09 mg/m³ Skin	STEL: 0.2mg/m³ TWA: 0.1mg/m³

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Carbonic acid, calcium salt (1:1) 471-34-1	-	TWA: 10mg/m ³	-	TWA: 10 mg/m ³
Carbon black 1333-86-4	TWA: 3mg/m ³	TWA: 3.5mg/m ³	3 mg/m³ TWA (inhalable particulate matter)	TWA: 3.5 mg/m ³
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	TWA: 0.1mg/m³ STEL: 0.2mg/m³	STEL: 0.2mg/m ³ TWA: 0.1mg/m ³	0.2 mg/m³ STEL (as Sn) 0.1 mg/m³ TWA (as Sn)	Skin STEL: 0.2 mg/m³ TWA: 0.1 mg/m³

8.2. Exposure controls

US - EN Page 5 / 12

SM7713 MS BLACK
Revision Number 1

Revision date 02-Apr-2021
Supersedes Date: 08-Jan-2021

OTHER INFORMATION

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³
		(vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m³	STEL: 250 ppm STEL: 325 mg/m³
		(vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m³	
		(vacated) S*	

Chemical name	Argentina	Brazil	Chile	Colombia
Methyl alcohol 67-56-1	TWA: 200 ppm Skin STEL: 250 ppm	TWA: 156 ppm TWA: 200 mg/m³ Skin	TWA: 175 ppm TWA: 229 mg/m³ Skin	STEL: 250ppm TWA: 200ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Methyl alcohol 67-56-1	TWA: 200ppm STEL: 250ppm	STEL: 250ppm STEL: 328mg/m³	250 ppm STEL 200 ppm TWA	Skin STEL: 250 ppm TWA: 200 ppm
		TWA: 200ppm TWA: 262mg/m³		

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). If splashes are likely to occur, wear

safety glasses with side-shields.

Hand protection Wear suitable gloves. The selection of suitable gloves does not only depend on the

material, but also on further marks of quality and various manufacturers.

Skin and body protection Wear suitable protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

US - EN Page 6/12

SM7713 MS BLACK
Revision Number 1 Supersedes Date: 02-Apr-2021
Supersedes Date: 08-Jan-2021

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash hands before breaks and after work. Take off contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical stateSolidAppearancePasteColorBlackOdorOdorlessOdor thresholdNot applicable

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pHNo data availableNone knownMelting point / freezing pointNo data availableNone knownBoiling point / boiling rangeNo data availableNone known

Flash point \Rightarrow 140 °C / 284 °F

Evaporation rateNo data availableNone knownFlammability (solid, gas)No data availableNone knownFlammability Limit in AirNone known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressure No data available None known Relative vapor density No data available None known Relative density No data available None known Water solubility Insoluble in water None known Solubility(ies) No data available None known **Partition coefficient** No data available None known **Autoignition temperature** No data available None known **Decomposition temperature** No data available None known Kinematic viscosity No data available None known **Dynamic viscosity** No data available None known

9.2. Other information

Explosive propertiesNo information availableOxidizing propertiesNo information availableSolvent content (%)No information available

Solid content (%) >= 97

Softening PointNo information availableMolecular weightNo information available

VOC Content (%) <20 g/L / 2 % EPA Method 24

Density 1.65 g/cm³

Bulk density No information available

10. Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

US - EN Page 7/12

SM7713 MS BLACK
Revision Number 1

Revision date 02-Apr-2021
Supersedes Date: 08-Jan-2021

10.2. Chemical stability

Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon monoxide Carbon dioxide (CO2) Nitrogen oxides (NOx) Small amounts of methanol

(CAS 67-56-1) are formed by hydrolysis and released upon curing

11. Toxicological information

11.1. Information on toxicological effects

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact May cause sensitization by skin contact. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 27,138.20 mg/kg ATEmix (inhalation-vapor) 675.1755 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Limestone	>5000 mg/kg (Rattus)	-	-
1317-65-3			
Carbonic acid, calcium salt (1:1)	LD50 > 2000 mg/kg (Rattus)	LD50 >2000 mg/kg (Rattus)	LC50 (4h) >3mg/ml (Rattus)
471-34-1	OECD 420	OECD 402	
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3360 μL/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)

US - EN Page 8/12

SM7713 MS BLACK Revision Number 1 Revision date 02-Apr-2021 Supersedes Date: 08-Jan-2021

2768-02-7	(Rattus) OECD 401	cuniculus)	OECD TG 403
N-(3-(trimethoxysilyl)propyl)ethy lenediamine 1760-24-3	=2295 mg/kg (Rattus)	>2000 mg/Kg (Rattus)	LC50 4H (Aerosol)1.5 - 2.44 mg/L air
Carbon black 1333-86-4	LD50 > 8000 mg/kg (Rattus) OECD 401	> 3 g/kg (Oryctolagus cuniculus)	> 4.6 mg/m ³ (Rat) 4 h
Tin, dibutylbis(2,4-pentanedionato-O ,O')-, (OC-6-11)- 22673-19-4	LD50 = 1864 mg/kg (Rattus) OECD 401	LD50 > 2000 mg/kg (Rattus) OECD 402	LC50 4hr: 16.8 mg/l (Rattus) (OECD TG 403)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768		,			
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute	Rabbit	eye		24 hours	Non-irritant
Eve Irritation/Corrosion]			

Respiratory or skin sensitization

May cause sensitization by skin contact.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitization	Guinea pig	Dermal	Not a skin sensitizer

N-(3-(trimethoxysilyl)propyl)ethylenediamine (1760-24-3)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	sensitizing
Sensitization			-

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation	in vitro	Not mutagenic
Test		

Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)- (22673-19-4)

Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell	in vitro	Mutagenic
Gene Mutation Test		

Carcinogenicity

Based on available data, the classification criteria are not met. As Carbon black (1333-86-4) is inextricably bound in the polymer matrix, it is not expected to be available as an airborne hazard (dust, mist, or spray) under normal condition of uses.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Carbon black	A3	Group 2B	-	X

US - EN Page 9/12

SM7713 MS BLACKRevision date02-Apr-2021Revision Number 1Supersedes Date:08-Jan-2021

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

1333-86-4

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

Contains a known or suspected reproductive toxin. May cause harm to breast-fed children.

Trimethoxyvinylsilane (2768-02-7)

Trimetrioxy virry londric (27 00 02 7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapor		90 days	0.058 NOAEL
Subchronic Inhalation					
Toxicity: 90-day Study					

Target organ effects Eyes, Lungs, Respiratory system, Skin.

Aspiration hazard Based on available data, the classification criteria are not met.

Other adverse effects

No information available.

Interactive effects

No information available.

12. Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Limestone 1317-65-3	CE50 (72h) >200mg/L Algae (Desmondesmus	CL50 (96h)>10000mg/L (Oncorhynchus mykiss)	-	CE50 (48h) >1000 mg/L Daphnia Magna
Carbonic acid, calcium salt (1:1) 471-34-1	subspicatus) IC50 72H Algae >1000 mg/l	CL50 96H >1000 mg/l	-	EC50 48H Daphnia >1000 mg/l
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)
N-(3-(trimethoxysilyl)prop yl)ethylenediamine 1760-24-3	-	LC50 (96H) =597 mg/L (Danio rerio)Semi-static	-	EC50 (48h) =81mg/L Daphnia magna Static
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus	>1000 mg/l (Brachydanio rerio) OCDE 203	-	EC50: >5600mg/L (24h, Daphnia magna)

US - EN Page 10 / 12

SM7713 MS BLACK
Revision Number 1

Revision Number 1

Revision date 02-Apr-2021
Supersedes Date: 08-Jan-2021

	subspicatus) OECD 202			
Tin, dibutylbis(2,4-pentanedio nato-O,O')-, (OC-6-11)- 22673-19-4	>2.0 mg/l	>2.0 mg/l	-	EC50 0.0036 mg/l 48Hr (Daphnia magna)

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Limestone 1317-65-3	0.9
Trimethoxyvinylsilane 2768-02-7	1.1
N-(3-(trimethoxysilyl)propyl)ethylenediamine 1760-24-3	-0.3

12.4. Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

13. Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

14. Transport information

DOT Not regulated

IATA Not regulated

<u>IMDG</u> Not regulated

15. Regulatory information

International Inventories

US - EN Page 11 / 12

SM7713 MS BLACK Revision Number 1 Revision date 02-Apr-2021 Supersedes Date: 08-Jan-2021

·

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

California Proposition 65

This product contains one or more of the substances listed on Proposition 65 at or above 0.1 wt.%

Chemical Name	CAS NO
Furan	110-00-9
Hexane	110-54-3
Carbon Black	1333-86-4
Quartz	14808-60-7
Methyl alcohol	67-56-1
Di-isodecyl phthalate	68515-49-1
Acetaldehyde	75-07-0
Propylene Oxide	75-56-9

Europe

Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

SVHC: Substances of Very High Concern for Authorization:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No	SVHC candidates
Tin, dibutylbis(2,4-pentanedionato-O,O')-, (OC-6-11)-	22673-19-4	X
2-(2H-benzotriazol-2-yl)-4,6-ditertpentylphenol	25973-55-1	X

16. Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation

US - EN Page 12 / 12

SM7713 MS BLACK
Revision Number 1

Revision Number 1

Revision date 02-Apr-2021
Supersedes Date: 08-Jan-2021

Prepared By Product Safety & Regulatory Affairs.

Revision date 02-Apr-2021

Revision note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

US - EN Page 13 / 12